



Main

Range of product	Actassi
Product or component type	Patch cord

Complementary

Type of cable	4 pair cables
Flame retardance	CM
Cable shielding type	UTP
Communication network category	6
Return loss	27 dB
Attenuation	0.1 dB
Near end crosstalk	55.1 dB
Power Sum Near End Crosstalk (PS NEXT)	52 dB
Far end crosstalk (FEXT)	49.8 dB
Power sum far end crosstalk	46.9 dB
Number of matings	1000 cycles
Rated voltage	150 V AC
[In] rated current	1.5 A
Insulation resistance	500 MOhm
Contact resistance	10 mOhm
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Colour tint	Blue
Cable length	5 m

Environment

Standards	IEC 60603-7 ISO/IEC 11801 2nd edition FCC part 68 subpart F TIA/EIA-568-B AS/NZS 3080:2003
-----------	--

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Product Environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------
