



Main

| | |
|---------------------------|----------------------|
| Range | Actassi |
| Product or component type | Patch panel |
| Provided equipment | With RJ45 connectors |

Complementary

| | |
|--------------------------------|---------------------------|
| Communication network category | 6 |
| Number of port | 24 ports UTP |
| Number of matings | 1000 cycles |
| [In] rated current | <= 1.5 A |
| Insulation resistance | >= 200 mOhm |
| Contact resistance | 1 mOhm |
| Product compatibility | Standard 19" cabinet/rack |

Environment

| | |
|---------------------------------------|--|
| Ambient air temperature for operation | -40...70 °C |
| Ambient air temperature for storage | -20...60 °C |
| Relative humidity | <= 93 % |
| Standards | ANSI/TIA/EIA-568-B ISO/IEC 11801 Ed.2, 2002 |

Offer Sustainability

| | |
|----------------------------------|--|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.